

# Thermal Label Printer

Model : WTPTI3409E

The WTPTI3409E industrial thermal label printer is a great value option for 4" wide, 300 dpi light industrial label printing. The WTPTI3409E features a small footprint, easily understandable operator interface and a full set of options to meet nearly every printing application. Its compact design, quiet operation and fast label throughput is equally at home, in the office or on the shop floor.

The printer's all-metal construction and die-cast aluminium print mechanism engine is durable enough to withstand the toughest production environments and is designed for years of trouble free use.

## FEATURES

- 1D and 2D barcode printing
- large ribbon capacity, 450 m long, max. O.D. 81.3 mm, 1" core
- (ink coated outside or inside)
- robust die-cast based print mechanism and metal cover with large clear media view window
- 256 MB flash memory and 256 MB SDRAM
- gap transmissive sensor (position adjustable)
- black mark reflective sensor (position adjustable)
- ribbon encoder sensor
- ribbon end sensor
- head open sensor
- media width 20 ~ 120 mm
- label length 5 ~ 11,430 mm
- media core diameter 25.4 mm ~ 76.2 mm
- media roll O.D 203 mm (based on a 25.4 mm core)
- media type: continuous, die-cut, black mark, fan-fold, notched (outside wound)
- compatible with EPL, ZPL, ZPLII and DPL printer languages
- includes Bartender Ultralite label design software compatible with Microsoft Windows (not compatible with MAC OS)



## SPECIFICATIONS

Model Number	Print Resolution	Max Print Speed	Max Print Width	Overall Dimensions (mm)
WTPTI3409E	300 dpi	228 mm / second (9 ips)	105 mm	248 (W) x 436 (D) x 274 (H)

Specifications may change without notice

## LABELLING EQUIPMENT

# Thermal Label Printer

Model: WTPTI3409E

## SPECIFICATIONS

Print Method - Direct Thermal	Yes
Print Method - Thermal Transfer	Yes
Printer Type	Industrial
Print Head Type	Flat Head
Maximum Print Speed	228 mm (9 inches) per second
Maximum Print Width	105 mm (4 inches)
Maximum Label Width	120 mm
Maximum Ribbon Length	450 m
Maximum Ribbon Width	40 mm ~ 110 mm
Ribbon Wind Direction	ink coated outside wound, ink coated inside wound
Ribbon Core Size	1inch (25.4 mm)
Communication Type:	Serial RS232 Ethernet 10/100 Mbps USB 2.0 USB host for scanner or PC keyboard Wireless 802.11 a/b/g/n (option) GPIO interface (option)
Bartender Ultralite	Yes
Peel & Present	Additional Option
Overall Dimensions (mm)	248 (W) x 436 (D) x 274 (H)
Net Weight	9 kg



Specifications may change without notice

## LABELLING EQUIPMENT

LABELS | LABELLING EQUIPMENT | PACKAGING EQUIPMENT  
ESL & DIGITAL SIGNAGE | WEIGHING SCALES | POS SYSTEMS  
FOOD EQUIPMENT | MAINTENANCE & REPAIRS | HIRE

1300 970 111  
enquiries@wedderburn.com.au  
www.wedderburn.com.au